

Hydraulic Nut Splitters


▼ Shown from left to right: NC-3241, NC-1319, NC-1924




- Compact and ergonomic design, easy to use
- Unique angled head design
- Single-acting, spring return cylinder
- Heavy duty chisels can be reground
- Applications include service trucks, piping industry, tank cleaning, petrochemical, steel construction, mining, etc.



◀ Easily removing rusty nuts during railroad construction is just one of many application examples for the Enerpac Nut Splitter.

 Nut Splitters include a spare chisel, a spare set screw and the wrench used to secure the chisel. A CR-400 coupler is standard.

Bolt Range (mm)	Hexagon Nut Range (mm)	Capa- city ton	Oil Capa- city (cm ³)	Model Number	Dimensions (mm)						 (kg)	Replacement Chisel Model Number
					A	B	C	D	F	H		
M6-M12	10 - 19	5	15	NC-1319	40	170	7	19	28	48	1,2	NCB-1319
M12-M16	19 - 24	10	20	NC-1924*	54	191	10	26	40	62	2,0	NCB-1924
M16-M22	24 - 32	15	60	NC-2432*	64	222	13	29	51	72	3,0	NCB-2432
M22-M27	32 - 41	20	80	NC-3241*	75	244	17	36	66	88	4,4	NCB-3241
M27-M33	41 - 50	35	155	NC-4150	94	288	21	45	74	105	8,2	NCB-4150
M33-M39	50 - 60	50	240	NC-5060	106	318	23	54	90	128	11,8	NCB-5060
M39-M48	60 - 75	90	492	NC-6075	156	393	26	72	110	181	34,1	NCB-6075

Ordering Notes: Maximum allowable hardness to split is HRC-44. Not to be used on square nuts.


NC, STN Series



Capacity:
5 - 90 ton

Bolt Range:
M6 - M48

Maximum Operating Pressure:
700 bar

 **Tool and Pump Sets**
Hydraulic Nut Splitters are available as sets (pump, gauge, gauge adaptor, couplers and hose) for your ordering convenience.

Nut Splitter Modelnr.	Handpump Modelnr.	Set Model Number
NC-1924	P-392	STN-1924H
NC-2432	P-392	STN-2432H
NC-3241	P-392	STN-3241H

